## MASON PRODUCT DATA SHEET



## Available Sizes 245x75x8mm

$oldsymbol{arOmega}$ Recycled Content	Up to 40%
Range	Mason
Category	Colour
Collection	Laura Ashley Collection
Short Code	LAMA4A
Colour	Twine
Finish	Gloss
Wall Suitability	Internal Only
Floor Suitability	-
Wet Barefoot	-
Material	Glazed Ceramic
Classificiation	BIII
Light Reflectance Value	54.00
CSV	V2

Sam	ples	Serv	ice
Jaiii	pics	201 4	

Tel: +44 (0) 1782 524 043 Fax: +44 (0) 1782 577 379

Email: samples@johnson-tiles.com

## Technical Helpline

Tel: +44 (0) 1782 524 111 Fax: +44 (0) 1782 577 379

Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

Physical Properties				
Test / Standard	Requirement	Test Result		
Length/Width EN ISO 10545-2	±0.5%≤ ± 2mm	Pass		
Thickness EN ISO I 0545-2	±10%≤±0.5mm	Pass		
Straightness of Sides EN ISO 10545-2	±0.3% ≤ ± 1.5mm	Pass		
Rectangularity EN ISO 10545-2	±0.5% ≤ ± 2mm	Pass		
Surface Flatness EN ISO 10545-2	±0.5% ≤ ± 2mm	Pass		
Water Absorption EN ISO 10545-3	10% to 20%	Pass		
Modulus of Rupture EN ISO 10545-4	Ave I5N/mm²	Pass		
Frost Resistance Not Applicable	N/A	Not suitable		
Chemical Resistance EN ISO 10545-13	Min Class B	Pass		
Stain Resistance EN ISO 10545-14	Min Class 3	Pass		
Fire Rating		Class A1 Non Combustible		
kg Weight/m² Thickness 8mm		16.12kg		



