

GLAZED VITRIFIED | WALL TILES

STONE INTRO










COUNTRY STONES

🗞 SIX COLOURS 🛛 TWO SIZES 🖓 ONE FINISH

Country Stones is a small format ceramic wall tile range with a rustic effect, designed to create a comforting, cottage feel. The natural colour palette echoes this rural sentiment with shades including Clay Brown, an earthy welcoming shade, Millstone White, a light comforting tone, and Summer Storm for statement depth. Country Stones mirrors the look of natural stone, making this range perfect to pair outdoor influences with cottage chic.









COLOURS AND PRODUCT CODES

V2: Low to High Shade Variation



CLAY BROWN [LRV: 24] Product Code: S COSOIA



 MILLSTONE WHITE
 LRV: 62

 Product Code:
 S
 COS03A



DOVETAILLRV: 53Product Code:SCOS04A



HEARTH GREY LRV: 31 Product Code: S COS05A




SUMMER STONE LRV: 16 Product Code: § COS06A



MIDNIGHTLRV: 08Product Code:SCOS07A

SIZE FORMATS AND AVAILABILITY

Size Options and Packing Information



#	Size Format	Thickness	Finish	Availability	Class	Pcs / Box	M² / Box	Kg/Box
01	200x100mm	6.5mm	S Satin	Dovetial, Millstone White and Clay Brown Only	Blla	50 Tiles	1.00 m ²	10.80 kg
02	100x100mm	6.5mm	S Satin	Dovetail, Clay Brown, Hearth Grey, Summer Storm and Midnight Only	Blla	100 Tiles	1.00 m ²	12.60 kg

Note: Glazed Vitrified / Blla tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - www.johnson-tiles.com.



TECHNICAL SUPPORT

Specification, Sustainability and Important Information

Product Specification

Range Name	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	Material / Class
Country Stones	S Satin	Internal Only	-	-	Glazed Vitrified / BIIa

Physical Properties - Glazed Ceramic / Blla

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
Length / Width EN ISO 10545-2	± 0.5% ≤ ± 2mm	Pass	Modulus of Rupture EN ISO 10545-4	Min. I 5N / mm²	Pass
→ Thickness EN ISO 10545-2	± 10% ≤ ± 0.5mm	Pass	Thermal Shock EN ISO 10545-9	Pass	Pass
Straightness of Side EN ISO 10545-2	± 0.3% ≤ ± 1.5mm	Pass	Frost Resistance EN ISO 10545-12	-	Not Suitable
Rectangularity EN ISO 10545-2	± 0.5% ≤ ± 2mm	Pass	Chemical Resistance EN ISO 10545-13	Min. Class B	Pass
→ Surface Flatness ►N ISO 10545-2	± 0.5% ≤ ± 2mm	Pass	Stain Resistance EN ISO 10545-14	Min. Class 3	Pass
Water Absorption EN ISO 10545-3	10% to 20%	Pass	Fire Rating		Class A I Non Combustible

Sustainability Credentials

Range Name	Material / Class	EPD	Recycled Content - Tiles	Recycled Content - Packaging
Country Stones	Glazed Vitrified / BIIa	-	Up to 10%	-

Note: Please contact our technical helpline, or visit our website for specification and installation advice. EPD: Environmental Product Declaration. CSV: Colour Shade Variation.

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour and patterning are acceptable.

The tiles shown in this literature are quality products and conform to BS EN 14411 as shown in the physical properties listed above.

For a comprehensive colour, size, finish and availability overview along with full technical and sustainability information for all products shown, please visit our website - www.johnson-tiles.com

- All sizes listed are metric modular.
- For specific suitability details, please contact our technical advice helpline or use the email address provided.
- Johnson Tiles Limited cannot accept responsibility for any tiles that have already been fixed.
- Johnson Tiles Limited reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

All product technical values quoted in this literature are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles Limited are British Standard registered. To find out more, please contact our technical advice helpline on +44 (0) 1782 524 | | | or email: technical@johnson-tiles.com.

WHERE TO FIND US

Head Office

Harewood Street, Tunstall, Stoke on Trent, Staffordshire, ST6 5JZ, United Kingdom

Tel: +44 (0) I 782 575 575 Email: info@johnson-tiles.com www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street, London, WIW 8BB, United Kingdom

Tel: +44 (0)20 7436 8629 Email: info@material-lab.co.uk www.material-lab.co.uk

Factory Outlet

Tel: +44 (0)1782 524 040 Email: foutlet@johnson-tiles.com www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0) 1782 524 000 Email: sales@johnson-tiles.com 8:30am - 4:30pm (Monday - Friday)

Order A Sample Tel: +44 (0)1782 524 043 Email: samples@johnson-tiles.com

Technical Advice Helpline Tel: +44 (0)1782 524 111 Email: technical@johnson-tiles.com

Updated: October 2024

