

ZEYA

GLAZED PORCELAIN | FLOOR & WALL TILES

STONE SELECT



ZEYA



FOUR COLOURS



SIX SIZES



THREE FINISHES

Zeya is a stone-effect range of glazed porcelain floor and wall tiles, combining both form and function with four muted tones of Chalk, Light Grey, Taupe and Dark Grey and three finishes – Natural, Grip and Grip+ 2cm. The Natural finish is minimalist in its luxury; while the Grip and Grip+ 2cm finishes provide a PTV 36+ slip resistance rating, making it ideal for commercial applications. Zeya features six large-format sizes ranging from 450x450mm up to 1200x600mm, try mixing sizes and colours for a truly unique installation.







Colours & Product Codes

V3: Moderate to High Shade Variation



CHALK LRV: 54 PEI: IV

Product Code - All Sizes: **N** ZEY01N | Product Code - 1200x600mm & 745x745mm: **G** ZEY01G



LIGHT GREY LRV: 55 PEI: IV

Product Code - All Sizes: **N** ZEY02N | Product Code - 1200x600mm & 745x745mm: **G** ZEY02G



Colours & Product Codes

V3: Moderate to High Shade Variation



TAUPE LRV: 41 PEI: III

Product Code - All Sizes: N ZEY03N | Product Code - 1200x600mm & 745x745mm: G ZEY03G

Product Code - 592x592mm: E ZEY03E 2cm



DARK GREY LRV: 32 PEI: III


Product Code - All Sizes: N ZEY04N | Product Code - 1200x600mm & 745x745mm: G ZEY04G

Product Code - 592x592mm: E ZEY04E 2cm



Size Formats

Sizing & Packing Information



#	Size	Thickness	Finish	Structure	Class	Pcs / Box	M2 / Box	Kg / Box
1	1200x600mm	10mm	(N) Natural	-	Bla	2 Tiles	1.44 m ²	31.10 kg
			(G) Grip	-	Bla	2 Tiles	1.44 m ²	31.10 kg
2	1000x1000mm	10mm	(N) Natural	-	Bla	2 Tiles	2.00 m ²	44.58 kg
3	745x745mm	9.7mm	(N) Natural	-	Bla	2 Tiles	1.12 m ²	21.98 kg
			(G) Grip	-	Bla	2 Tiles	1.12 m ²	21.98 kg
4	600x600mm	9.5mm	(N) Natural	-	Bla	4 Tiles	1.44 m ²	29.16 kg
	592x592mm	20mm	(E) Grip+ 2cm	-	Bla	2 Tiles	0.72 m ²	27.50 kg
5	600x300mm	8.7mm	(N) Natural	-	Bla	7 Tiles	1.26 m ²	22.92 kg
6	450x450mm	8.5mm	(N) Natural	-	Bla	7 Tiles	1.41 m ²	25.10 kg

Note: (R) Rectified Edge. Class Bla: Glazed Porcelain Tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - www.johnson-tiles.com.



Taupe Natural 745x745x9.7mm - ZEY03N
Light Grey Natural 600x300x8.7mm - ZEY02N



Technical, Sustainability & Important Information

Specification

Range	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material / Class
Zeya	N Natural	Internal & External	Internal Only	-	V3	Glazed Porcelain [Bla]
	G Grip	Internal & External	Internal & External	Yes	V3	Glazed Porcelain [Bla]
	E Grip+ 2cm	Internal & External	Internal & External	Yes	V3	Glazed Porcelain [Bla]

Floor Values

Finish	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
N Natural	Chalk & Light Grey	Dry 36+ Wet 25 - 35	-	-	-	IV	Commercial
	Taupe & Dark Grey	Dry 36+ Wet 25 - 35	-	-	-	III	Light Commercial
G Grip	Chalk & Light Grey	Dry 36+ Wet 36+	Wet 36+	-	-	IV	Commercial
	Taupe & Dark Grey	Dry 36+ Wet 36+	Wet 36+	-	-	III	Light Commercial
E Grip+ 2cm	Chalk & Light Grey	Dry 36+ Wet 36+	Wet 36+	-	-	IV	Commercial
	Taupe & Dark Grey	Dry 36+ Wet 36+	Wet 36+	-	-	III	Light Commercial

Physical Properties

Test & Standard	Requirement	Test Result	Test & Standard	Requirement	Test Result	
Length / Width EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	Modulus of Rupture EN ISO 10545 - 4	Min. 35N / mm ²	$\geq 35\text{N} / \text{mm}^2$	
Thickness EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	Thermal Shock EN ISO 10545 - 9	Pass	Pass	
Straightness of Side EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	Frost Resistance EN ISO 10545 - 12	Resistant	Resistant	
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class B	
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 3	
Water Absorption EN ISO 10545 - 3	$\leq 0.5\%$	$\leq 0.5\%$	Fire Rating	-	Class A I _{FL} Non Combustible	
Weight / M ²	22.30 kg 10mm thick	19.63 kg 9.7mm thick	20.25 kg 9.5mm thick	18.20 kg 8.7mm thick	17.80 kg 8.5mm thick	38.20 kg 20mm thick

Sustainability Information

Range	Material / Class	EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Zeya	Glazed Porcelain [Bla]	Yes	-	Up to 100%	Up to 100%

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications.

Please contact our technical helpline for specification and installation advice. All glazed porcelain [Bla] products shown in this range overview conform to BS EN 14411.

CSV: Colour Shade Variation. PTV (4S): Pendulum Test Value - Slider 96. PTV (TRL): Pendulum Test Value - Slider 55. R Value (DIN 51130). Wet Ramp (DIN 51097).

PEI: Porcelain Enamel Institute. EPD: Environmental Product Declaration. For a full company sustainability overview please visit www.johnson-tiles.com/about/sustainability.

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles, several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed. For a comprehensive colour, size and finish overview along with full technical and sustainability information for all of the product shown in this product presenter, please visit our website - www.johnson-tiles.com.

- All sizes shown are metric modular.
- For specific suitability details please contact our technical department.
- Johnson Tiles cannot accept responsibility for tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does/will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2023 Johnson Tiles. All rights reserved.



All product technical values quoted in this product presenter are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles are British Standard registered and all products conform to the standards set in BS EN 14411.

For the reassurance of single-source supply, Johnson Tiles offers a free of charge NBS M40 specification writing service featuring the Norcros Adhesives range of tile fixing products. To find out more or for any questions or queries relating to any tile related technical information featured in this product presenter, please contact our technical advice helpline on +44 (0)1782 524 111 or email ddunlop@johnson-tiles.com

The colours shown in this sample tile wallet and attached booklet are as accurate as printing processes will allow. Please refer to actual product samples before specifying. Every effort has been made to ensure the accuracy of the information given.

For more information about **Zeya** or any
of our other product ranges simply visit
www.johnson-tiles.com |       

Where To Find & Contact Us

Johnson Tiles Head Office

Harewood Street, Tunstall,
Stoke on Trent, Staffordshire,
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575
Email: info@johnson-tiles.com
www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street,
London, W1W 8BB,
United Kingdom

Tel: +44 (0)20 7436 8629
Email: info@material-lab.co.uk
www.material-lab.co.uk

Johnson Tiles Factory Outlet

Tel: +44 (0)1782 524 040
Email: foutlet@johnson-tiles.com
www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0)1782 524 000
Email: sales@johnson-tiles.com

Order A Sample

Tel: +44 (0)1782 524 043
Email: samples@johnson-tiles.com

Technical Advice

Tel: +44 (0)1782 524 111
Email: ddunlop@johnson-tiles.com

Launched: May 2023

www.johnson-tiles.com |       

JOHNSON • TILES 
MADE IN THE UK SINCE 1901

Johnson Tiles is a division of Norcros Group (Holdings) Limited,
Ladyfield House, Station Road, Wilmslow, Cheshire, SK9 1BU,
United Kingdom. Registered in England number 566694.