

ALLURE

GLAZED PORCELAIN AND CERAMIC | FLOOR AND WALL TILES

MARBLE STRUCTURE SELECT



f X IG DJ P in Y

www.johnson-tiles.com

© 2024 Johnson Tiles Limited

Est. 1901
**JOHNSON
TILES**

ALLURE



ONE COLOUR



EIGHT SIZES



TWO FINISHES

A sumptuous, eye-catching range of glazed porcelain and ceramic floor and wall tiles, Allure showcases a beautiful warm carrara marble effect in two stunning finishes. Contemporary décors of on-trend star and chevron shapes provide luxurious motifs for this classic marble range, keying into the ever-popular trend for geometric designs. Ranging from wall tile options in a 600x300mm size to the elongated format of 2600x1200mm for the floor, Allure offers a variety of sleek size options for modern interior commercial spaces.





COLOURS AND PRODUCT CODES

V2: Low to Moderate Shade Variation



WHITE / GOLD PEI: IV LRV: 80

Product Code (Bla): P ALL01P | Product Code (BIII): G ALL01A | Fitting Code (Bla): P ALLIPS

COLOURS AND PRODUCT CODES

V2: Low to Moderate Shade Variation



WHITE / GOLD - WEAVE LRV: 80

Product Code (BIII): G ALL01W



WHITE / GOLD - CHEVRON LRV: 80

Product Code (BIII): G ALL01V




WHITE / GOLD - STAR LRV: 80

Product Code (BIII): G ALL01S

SIZE FORMATS AND AVAILABILITY


Size Options and Packing Information



#	Size Format	Thickness	Finish	Structure	Availability	Class	Pcs / Box	M ² / Box	Kg / Box
01	2600x1200mm	7mm	[P] Polished	-	All Colours Shown	Bla	1 Tile	3.12 m ²	52.00 kg
02	1600x800mm	9.7mm	[P] Polished	-	All Colours Shown	Bla	1 Tile	1.28 m ²	29.00 kg
03	1200x1200mm	9.3mm	[P] Polished	-	All Colours Shown	Bla	1 Tile	1.44 m ²	31.00 kg
04	1200x600mm	9.3mm	[P] Polished	-	All Colours Shown	Bla	2 Tiles	1.44 m ²	31.00 kg
				-	All Colours Shown	BIII	3 Tiles	1.44 m ²	28.00 kg
				Weave	All Colours Shown	BIII	3 Tiles	1.44 m ²	28.00 kg
				Chevron	All Colours Shown	BIII	3 Tiles	1.44 m ²	28.00 kg
05	1200x400mm	11mm	[G] Gloss	Star	All Colours Shown	BIII	3 Tiles	1.44 m ²	28.00 kg
				-	All Colours Shown	BIII	3 Tiles	1.44 m ²	28.00 kg
				Weave	All Colours Shown	BIII	3 Tiles	1.44 m ²	28.00 kg
06	800x800mm	9.7mm	[P] Polished	-	All Colours Shown	Bla	2 Tiles	1.44 m ²	27.00 kg
07	600x600mm	9.3mm	[P] Polished	-	All Colours Shown	Bla	3 Tiles	1.08 m ²	24.00 kg
08	600x300mm	9mm	[G] Gloss	-	All Colours Shown	BIII	7 Tiles	1.26 m ²	18.50 kg
				Weave	All Colours Shown	BIII	7 Tiles	1.26 m ²	18.50 kg

#	Fittings	Thickness	Finish	Structure	Availability	Class	Pcs / Box	Lm / Box	Kg / Box
09	600x100mm R/T Skirting	10mm	[P] Polished	-	All Colours Shown	Bla	15 Tiles	9.00 lm	21.00 kg

Note: Glazed Porcelain / Bla and Glazed Ceramic / BIII tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - www.johnson-tiles.com. (R) Rectified Edge.





White / Gold Polished 600x600x9.3mm - ALL01P


TECHNICAL SUPPORT

Specification, Sustainability and Important Information













Product Specification

Range Name	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	Material / Class
Allure	 Polished	Internal and External	Internal Only	-	Glazed Porcelain / Bla
	 Gloss	Internal Only	-	-	Glazed Ceramic / BIII













Floor Values

Finish	Colour	PTV (96)	PTV (55)	R Value	Wet Ramp	PEI	Traffic
 Polished	All Colours Shown	Wet 0 - 24	-	-	-	IV	Commercial

Physical Properties - Glazed Porcelain / Bla

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
 Length / Width EN ISO 10545-2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	 Modulus of Rupture EN ISO 10545-4	Min. 35N / mm ²	Pass
 Thickness EN ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	 Thermal Shock EN ISO 10545-9	Pass	Pass
 Straightness of Side EN ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	 Frost Resistance EN ISO 10545-12	Resistant	Resistant
 Rectangularity EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Chemical Resistance EN ISO 10545-13	Min. Class B	Pass
 Surface Flatness EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Stain Resistance EN ISO 10545-14	Min. Class 3	Pass
 Water Absorption EN ISO 10545-3	$\leq 0.5\%$	Pass	 Fire Rating		Class A I FL Non Combustible

Physical Properties - Glazed Ceramic / BIII

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
 Length / Width EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Modulus of Rupture EN ISO 10545-4	Min. 15N / mm ²	Pass
 Thickness EN ISO 10545-2	$\pm 10\% \leq \pm 0.5\text{mm}$	Pass	 Thermal Shock EN ISO 10545-9	Pass	Pass
 Straightness of Side EN ISO 10545-2	$\pm 0.3\% \leq \pm 1.5\text{mm}$	Pass	 Frost Resistance EN ISO 10545-12	-	Not Suitable
 Rectangularity EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Chemical Resistance EN ISO 10545-13	Min. Class B	Pass
 Surface Flatness EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Stain Resistance EN ISO 10545-14	Min. Class 3	Pass
 Water Absorption EN ISO 10545-3	10% to 20%	Pass	 Fire Rating		Class A I Non Combustible

Sustainability Credentials

Range Name	Material / Class	EPD	Recycled Content - Tiles	Recycled Content - Packaging
Allure	Glazed Porcelain / Bla	Yes	Up to 40%	Up to 100% (Boxes Only)
	Glazed Ceramic / BIII	Yes	Up to 40%	Up to 100% (Boxes Only)

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. Please contact our technical helpline, or visit our website for specification and installation advice. All floor tiles shown in this literature achieve a PTV (96) Dry 36+ test result. PTV (96): Pendulum Test Value - 4S. PTV (55): Pendulum Test Value - TRL. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute. EPD: Environmental Product Declaration. CSV: Colour Shade Variation.

TECHNICAL SUPPORT

Specification, Sustainability and Important Information

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour and patterning are acceptable.

The tiles shown in this literature are quality products and conform to BS EN 14411 as shown in the physical properties listed above.

For a comprehensive colour, size, finish and availability overview along with full technical and sustainability information for all products shown, please visit our website - www.johnson-tiles.com

- All sizes listed are metric modular.
- For specific suitability details, please contact our technical advice helpline or use the email address provided.
- Johnson Tiles Limited cannot accept responsibility for any tiles that have already been fixed.
- Johnson Tiles Limited reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

All product technical values quoted in this literature are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles Limited are British Standard registered. To find out more, please contact our technical advice helpline on +44 (0)1782 524 111 or email: technical@johnson-tiles.com.



Wall: White / Gold Polished 1600x800x9.7mm - ALL01P
Floor: White / Gold Polished 800x800x9.7mm - ALL01P

WHERE TO FIND US

Head Office

Harewood Street, Tunstall,
Stoke on Trent, Staffordshire,
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575
Email: info@johnson-tiles.com
www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street,
London, W1W 8BB,
United Kingdom

Tel: +44 (0)20 7436 8629
Email: info@material-lab.co.uk
www.material-lab.co.uk

Factory Outlet

Tel: +44 (0)1782 524 040
Email: foutlet@johnson-tiles.com
www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0)1782 524 000
Email: sales@johnson-tiles.com
8:30am - 4:30pm (Monday - Friday)

Order A Sample

Tel: +44 (0)1782 524 043
Email: samples@johnson-tiles.com

Technical Advice Helpline

Tel: +44 (0)1782 524 111
Email: technical@johnson-tiles.com

Updated: October 2024



www.johnson-tiles.com | [f](#) [X](#) [G](#) [d](#) [P](#) [in](#) [v](#)

© 2024 Johnson Tiles Limited