

CANVAS

GLAZED CERAMIC | WALL TILES

MARBLE STONE STRUCTURE SELECT



f X @ d p in v

www.johnson-tiles.com

© 2024 Johnson Tiles Limited

Est. 1901
**JOHNSON
TILES**

CANVAS



FIVE COLOURS




ONE SIZE



ONE FINISH

Canvas is a distinctive glazed ceramic wall tile collection, perfectly suited for both commercial and residential design projects. Available in five versatile neutral tones - Carrara, Ivory, Steel, Beige, and Grey - it offers a serene and elegant aesthetic for any busy space. The tiles come in a sleek matt finish and a practical 600x300mm size format, ensuring a timeless appeal. For added design versatility, the range includes structured options such as Rockfall, Linear and Chevron patterns. These can be used to complement the standard tiles subtly or take centre stage as striking feature elements.





Beige Chevron Matt 600x300x8.5mm - CAV04D




Steel Matt 600x300x8.5mm - CAV03A
Steel Linear Matt 600x300x8.5mm - CAV03D



Carrara Rockfall Matt 600x300x8.5mm - CAV01A
Carrara Linear Matt 600x300x8.5mm - CAV01D


COLOURS AND PRODUCT CODES

V3: Moderate to High Shade Variation



CARRARA - ROCKFALL LRV: 72

Product Code: **M** CAV01A



CARRARA - LINEAR LRV: 72

Product Code: **M** CAV01D



IVORY LRV: 64

Product Code: **M** CAV02A



IVORY - LINEAR LRV: 64

Product Code: **M** CAV02D



STEEL LRV: 32

Product Code: **M** CAV03A



STEEL - LINEAR LRV: 32

Product Code: **M** CAV03D

COLOURS AND PRODUCT CODES

V3: Moderate to High Shade Variation



BEIGE LRV: 62

Product Code:  CAV04A



BEIGE - CHEVRON LRV: 62

Product Code:  CAV04D




GREY LRV: 55

Product Code:  CAV05A



GREY - CHEVRON LRV: 55

Product Code:  CAV05D



Beige Matt 600x300x8.5mm - CAV04A

Beige Chevron Matt 600x300x8.5mm - CAV04D

SIZE FORMATS AND AVAILABILITY

Size Options and Packing Information

01



#	Size Format	Thickness	Finish	Structure	Availability	Class	Pcs / Box	M ² / Box	Kg / Box
01	600x300mm	8.5mm	[M] Matt	-	Ivory and Steel Only	BIII	9 Tiles	1.62 m ²	24.00 kg
				Rockfall	Carrara Only	BIII	9 Tiles	1.62 m ²	24.00 kg
				Linear	Carrara, Ivory and Steel Only	BIII	8 Tiles	1.44 m ²	24.00 kg
				-	Beige and Grey Only	BIII	8 Tiles	1.44 m ²	21.00 kg
				Chevron	Beige and Grey Only	BIII	8 Tiles	1.44 m ²	21.00 kg

Note: Glazed Ceramic / BIII tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - www.johnson-tiles.com. (R) Rectified.




Ivory Matt 600x300x8.5mm - CAV02A
Ivory Linear Matt 600x300x8.5mm - CAV02D













TECHNICAL SUPPORT

Specification, Sustainability and Important Information

Product Specification

Range Name	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	Material / Class
Canvas	 Matt	Internal Only	-	-	Glazed Ceramic / BIII

Physical Properties - Glazed Ceramic / BIII

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
 Length / Width EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Modulus of Rupture EN ISO 10545-4	Min. 15N / mm ²	Pass
 Thickness EN ISO 10545-2	$\pm 10\% \leq \pm 0.5\text{mm}$	Pass	 Thermal Shock EN ISO 10545-9	Pass	Pass
 Straightness of Side EN ISO 10545-2	$\pm 0.3\% \leq \pm 1.5\text{mm}$	Pass	 Frost Resistance EN ISO 10545-12	-	Not Suitable
 Rectangularity EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Chemical Resistance EN ISO 10545-13	Min. Class B	Pass
 Surface Flatness EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Stain Resistance EN ISO 10545-14	Min. Class 3	Pass
 Water Absorption EN ISO 10545-3	10% to 20%	Pass	 Fire Rating		Class A I Non Combustible

Sustainability Credentials

Range Name	Material / Class	EPD	Recycled Content - Tiles	Recycled Content - Packaging
Canvas	Glazed Ceramic / BIII	Yes	Up to 40%	Up to 100% (Boxes Only)

Note: Please contact our technical helpline, or visit our website for specification and installation advice.
EPD: Environmental Product Declaration. CSV: Colour Shade Variation.

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour and patterning are acceptable.

The tiles shown in this literature are quality products and conform to BS EN 14411 as shown in the physical properties listed above.

For a comprehensive colour, size, finish and availability overview along with full technical and sustainability information for all products shown, please visit our website - www.johnson-tiles.com

- All sizes listed are metric modular.
- For specific suitability details, please contact our technical advice helpline or use the email address provided.
- Johnson Tiles Limited cannot accept responsibility for any tiles that have already been fixed.
- Johnson Tiles Limited reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

All product technical values quoted in this literature are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles Limited are British Standard registered. To find out more, please contact our technical advice helpline on +44 (0)1782 524 111 or email: technical@johnson-tiles.com.

WHERE TO FIND US

Head Office

Harewood Street, Tunstall,
Stoke on Trent, Staffordshire,
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575
Email: info@johnson-tiles.com
www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street,
London, W1W 8BB,
United Kingdom

Tel: +44 (0)20 7436 8629
Email: info@material-lab.co.uk
www.material-lab.co.uk

Factory Outlet

Tel: +44 (0)1782 524 040
Email: foutlet@johnson-tiles.com
www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0)1782 524 000
Email: sales@johnson-tiles.com
8:30am - 4:30pm (Monday - Friday)

Order A Sample

Tel: +44 (0)1782 524 043
Email: samples@johnson-tiles.com

Technical Advice Helpline

Tel: +44 (0)1782 524 111
Email: technical@johnson-tiles.com

Updated: October 2024



www.johnson-tiles.com | [f](#) [X](#) [G](#) [d](#) [P](#) [in](#) [v](#)

© 2024 Johnson Tiles Limited