

ZION

UN-GLAZED PORCELAIN | FLOOR AND WALL TILES

STONE SELECT



www.johnson-tiles.com

© 2024-25 Johnson Tiles Limited

Est. 1901
**JOHNSON
TILES**

ZION



FOUR COLOURS




TWO SIZES



TWO FINISHES

Evoking neutral tones, Zion offers a classically simple stone-effect colour palette that conveys sophistication and elegance; from the lighter notes of Bone and Pebble to the richer shades of Flint and Basalt, Zion delivers clean lines and calming tones to achieve an opulent look. Featuring two finishes – Natural and Polished; and two large-format sizes of 600x600mm and 600x300mm, any combination from this range will easily lift the luxury of an installation. Zion achieves a PTV 36+ slip resistance rating through the Natural finish, which makes it well-suited for all residential and commercial applications.





Bone Polished 600x600x8.5mm - ZIN01P



Pebble Polished 600x600x8.5mm - ZIN02P



Basalt Polished 600x600x8.5mm - ZIN04P

COLOURS AND PRODUCT CODES

V2: Low to Moderate Shade Variation



BONE LRV: 53

Product Code: N ZIN01N + P ZIN01P




PEBBLE LRV: 40

Product Code: N ZIN02N + P ZIN02P


COLOURS AND PRODUCT CODES

V2: Low to Moderate Shade Variation



FLINT LRV: 22

Product Code: N ZIN03N + P ZIN03P




BASALT LRV: 13

Product Code: N ZIN04N + P ZIN04P

SIZE FORMATS AND AVAILABILITY

Size Options and Packing Information



#	Size Format	Thickness	Finish	Availability	Class	Pcs / Box	M ² / Box	Kg / Box
01	600x600mm	9.2mm	N Natural	All Colours Shown	Bla	4 Tiles	1.44 m ²	31.50 kg
		8.5mm	P Polished	All Colours Shown	Bla	4 Tiles	1.44 m ²	30.50 kg
02	600x300mm	9.2mm	N Natural	All Colours Shown	Bla	8 Tiles	1.44 m ²	31.50 kg
		8.5mm	P Polished	All Colours Shown	Bla	8 Tiles	1.44 m ²	30.50 kg

Note: Un-glazed Porcelain / Bla tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - www.johnson-tiles.com.





Pebble Polished 600x600x8.5mm - ZIN02P



TECHNICAL SUPPORT

Specification, Sustainability and Important Information













Product Specification

Range Name	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	Material / Class
Zion	 Natural	Internal and External	Internal Only	-	Un-glazed Porcelain / Bla
	 Polished	Internal and External	Internal Only	-	Un-glazed Porcelain / Bla

Floor Values

Finish	Colour	PTV (96)	PTV (55)	R Value	Wet Ramp	PEI	Traffic
 Natural	All Colours Shown	Wet 36+	-	R10	-	-	Commercial
 Polished	All Colours Shown	Wet 0 - 24	-	-	-	-	Commercial

Physical Properties - Un-glazed Porcelain / Bla

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
 Length / Width EN ISO 10545-2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	 Modulus of Rupture EN ISO 10545-4	Min. 35N / mm ²	Pass
 Thickness EN ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	 Thermal Shock EN ISO 10545-9	Pass	Pass
 Straightness of Side EN ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	 Frost Resistance EN ISO 10545-12	Resistant	Resistant
 Rectangularity EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Chemical Resistance EN ISO 10545-13	Min. Class B	Pass
 Surface Flatness EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Stain Resistance EN ISO 10545-14	Min. Class 3	Pass
 Water Absorption EN ISO 10545-3	$\leq 0.5\%$	Pass	 Fire Rating		Class A I FL Non Combustible

Sustainability Credentials

Range Name	Material / Class	EPD	Recycled Content - Tiles	Recycled Content - Packaging
Zion	Glazed Porcelain / Bla	Yes	-	Up to 100% (Boxes Only)

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. Please contact our technical helpline, or visit our website for specification and installation advice. All floor tiles shown in this literature achieve a PTV (96) Dry 36+ test result. PTV (96): Pendulum Test Value - 4S. PTV (55): Pendulum Test Value - TRL. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute. EPD: Environmental Product Declaration. CSV: Colour Shade Variation.

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour and patterning are acceptable.

The tiles shown in this literature are quality products and conform to BS EN 14411 as shown in the physical properties listed above.

For a comprehensive colour, size, finish and availability overview along with full technical and sustainability information for all products shown, please visit our website - www.johnson-tiles.com

- All sizes listed are metric modular.
- For specific suitability details, please contact our technical advice helpline or use the email address provided.
- Johnson Tiles Limited cannot accept responsibility for any tiles that have already been fixed.
- Johnson Tiles Limited reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

All product technical values quoted in this literature are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles Limited are British Standard registered. To find out more, please contact our technical advice helpline on +44 (0)1782 524 111 or email: technical@johnson-tiles.com.

WHERE TO FIND US

Head Office

Harewood Street, Tunstall,
Stoke on Trent, Staffordshire,
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575
Email: info@johnson-tiles.com
www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street,
London, W1W 8BB,
United Kingdom

Tel: +44 (0)20 7436 8629
Email: info@material-lab.co.uk
www.material-lab.co.uk

Factory Outlet

Tel: +44 (0)1782 524 040
Email: foutlet@johnson-tiles.com
www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0)1782 524 000
Email: sales@johnson-tiles.com
8:30am - 4:30pm (Monday - Friday)

Order A Sample

Tel: +44 (0)1782 524 043
Email: samples@johnson-tiles.com

Technical Advice Helpline

Tel: +44 (0)1782 524 111
Email: technical@johnson-tiles.com

Updated: February 2025



www.johnson-tiles.com | [f](#) [X](#) [G](#) [d](#) [P](#) [in](#) [v](#)

© 2024-25 Johnson Tiles Limited