

NORDIC WOOD

GLAZED PORCELAIN AND CERAMIC | FLOOR AND WALL TILES

WOOD STRUCTURE ABSOLUTE



www.johnson-tiles.com

© 2024 Johnson Tiles Limited

Est. 1901
**JOHNSON
TILES**

NORDIC WOOD



THREE COLOURS



TWO SIZES



ONE FINISH

Introducing Nordic Wood, our latest wood-effect range of wall and floor tiles. The classic porcelain 1200x200mm planks are paired with trendy ceramic 1200x600mm wall panels, available in three versatile colour options: Light Oak, Natural Oak, and Burnt Oak. Designed to create spaces filled with calm and harmony, Nordic Wood is perfect for opening up any residential or commercial area. With the Natural finish in the 1200x200mm size providing an impressive PTV 36+ slip resistance rating. The tiles feature rectified edges for a cleaner finish, along with matching skirtings for a seamless, complete look.





Natural Oak Natural | 200x200x9mm - NOR02N
Natural Oak Panelling Natural | 200x600x8.2mm - NOR02D



Light Oak Natural | 200x200x9mm - NOR01N

COLOURS AND PRODUCT CODES

V3: Moderate to High Shade Variation



LIGHT OAK PEI: II LRV: 31

Product Code (Bla): N NOR01N | Fitting Code (Bla): N NOR1NS



LIGHT OAK - PANELLING LRV: 31

Product Code (BIII): N NOR01D

COLOURS AND PRODUCT CODES

V3: Moderate to High Shade Variation



NATURAL OAK PEI: III LRV: 19

Product Code (Bla): N NOR02N | Fitting Code (Bla): N NOR2NS



NATURAL OAK - PANELLING LRV: 19

Product Code (BIII): N NOR02D

COLOURS AND PRODUCT CODES

V3: Moderate to High Shade Variation



BURNT OAK PEI: II LRV: 15

Product Code (Bla): N NOR03N | Fitting Code (Bla): N NOR3NS




BURNT OAK - PANELLING LRV: 15

Product Code (BIII): N NOR03D

SIZE FORMATS AND AVAILABILITY

Size Options and Packing Information



#	Size Format	Thickness	Finish	Structure	Availability	Class	Pcs / Box	M ² / Box	Kg / Box
01	1200x200mm	9mm	<input checked="" type="checkbox"/> Natural	-	All Colours Shown	Bla	5 Tiles	1.20 m ²	23.50 kg
02	1200x600mm	8.2mm	<input checked="" type="checkbox"/> Natural	Panelling	All Colours Shown	BIII	2 Tiles	1.44 m ²	21.00 kg

#	Fittings	Thickness	Finish	Structure	Availability	Class	Pcs / Box	Lm / Box	Kg / Box
03	1200x75mm R/T Skirting	9mm	<input checked="" type="checkbox"/> Natural	-	All Colours Shown	Bla	9 Tiles	10.80 lm	18.00 kg

Note: Glazed Porcelain / Bla and Glazed Ceramic / BIII tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - www.johnson-tiles.com. (R) Rectified Edge.



TECHNICAL SUPPORT

Specification, Sustainability and Important Information

Product Specification

Range Name	Finish	Structure	Wall Suitability	Floor Suitability	Wet Barefoot	Material / Class
Nordic Wood	N Natural	-	Internal and External	Internal Only	-	Glazed Porcelain / Bla
		Panelling	Internal Only	-	-	Glazed Ceramic / BIII

Floor Values

Finish	Structure	Colour	PTV (96)	PTV (55)	R Value	Wet Ramp	PEI	Traffic
N Natural	-	Natural Oak	Wet 36+	-	R 10	-	III	Light Commercial
		Light Oak and Burnt Oak	Wet 36+	-	R 10	-	II	Domestic

Physical Properties - Glazed Porcelain / Bla

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
Length / Width EN ISO 10545-2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	Modulus of Rupture EN ISO 10545-4	Min. 35N / mm ²	Pass
Thickness EN ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	Thermal Shock EN ISO 10545-9	Pass	Pass
Straightness of Side EN ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	Frost Resistance EN ISO 10545-12	Resistant	Resistant
Rectangularity EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Chemical Resistance EN ISO 10545-13	Min. Class B	Class B
Surface Flatness EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Stain Resistance EN ISO 10545-14	Min. Class 3	Pass
Water Absorption EN ISO 10545-3	$\leq 0.5\%$	$\leq 0.5\%$	Fire Rating		Class A I FL Non Combustible
Weight / M ²	19.59 kg 9mm Thick				

Physical Properties - Glazed Ceramic / BIII

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
Length / Width EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Modulus of Rupture EN ISO 10545-4	Min. 15N / mm ²	Pass
Thickness EN ISO 10545-2	$\pm 10\% \leq \pm 0.5\text{mm}$	Pass	Thermal Shock EN ISO 10545-9	Pass	Pass
Straightness of Side EN ISO 10545-2	$\pm 0.3\% \leq \pm 1.5\text{mm}$	Pass	Frost Resistance EN ISO 10545-12	-	Not Suitable
Rectangularity EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Chemical Resistance EN ISO 10545-13	Min. Class B	Class B
Surface Flatness EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Stain Resistance EN ISO 10545-14	Min. Class 3	Pass
Water Absorption EN ISO 10545-3	10% to 20%	$\geq 10\%$	Fire Rating		Class A I Non Combustible
Weight / M ²	14.59 kg 8.2mm Thick				

Sustainability Credentials

Range Name	Material / Class	EPD	Recycled Content - Tiles	Recycled Content - Packaging
Nordic Wood	Glazed Porcelain / Bla	Yes	Up to 40%	Up to 100% (Boxes Only)
	Glazed Ceramic / BIII	Yes	Up to 40%	Up to 100% (Boxes Only)

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. Please contact our technical helpline, or visit our website for specification and installation advice. All floor tiles shown in this literature achieve a PTV (96) Dry 36+ test result. PTV (96): Pendulum Test Value - 4S. PTV (55): Pendulum Test Value - TRL. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute. EPD: Environmental Product Declaration. CSV: Colour Shade Variation.

TECHNICAL SUPPORT

Specification, Sustainability and Important Information

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour and patterning are acceptable.

The tiles shown in this literature are quality products and conform to BS EN 14411 as shown in the physical properties listed above.

For a comprehensive colour, size, finish and availability overview along with full technical and sustainability information for all products shown, please visit our website - www.johnson-tiles.com

- All sizes listed are metric modular.
- For specific suitability details, please contact our technical advice helpline or use the email address provided.
- Johnson Tiles Limited cannot accept responsibility for any tiles that have already been fixed.
- Johnson Tiles Limited reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

All product technical values quoted in this literature are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles Limited are British Standard registered. To find out more, please contact our technical advice helpline on +44 (0)1782 524 111 or email: ddunlop@johnson-tiles.com.



Light Oak Panelling Natural 1200x600x8.2mm - NOR01D

WHERE TO FIND US

Head Office

Harewood Street, Tunstall,
Stoke on Trent, Staffordshire,
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575
Email: info@johnson-tiles.com
www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street,
London, W1W 8BB,
United Kingdom

Tel: +44 (0)20 7436 8629
Email: info@material-lab.co.uk
www.material-lab.co.uk

Factory Outlet

Tel: +44 (0)1782 524 040
Email: foutlet@johnson-tiles.com
www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0)1782 524 000
Email: sales@johnson-tiles.com
8:30am - 5:00pm (Monday - Friday)

Order A Sample

Tel: +44 (0)1782 524 043
Email: samples@johnson-tiles.com

Technical Advice Helpline

Tel: +44 (0)1782 524 111
Email: ddunlop@johnson-tiles.com

Launched: September 2024



www.johnson-tiles.com | [f](#) [X](#) [G](#) [d](#) [P](#) [in](#) [v](#)

© 2024 Johnson Tiles Limited