

ATRIUM

GLAZED PORCELAIN | FLOOR AND WALL TILES

CONCRETE MOSAIC SELECT



www.johnson-tiles.com

© 2024 Johnson Tiles Limited

Est. 1901
**JOHNSON
TILES**

ATRIUM



FOUR COLOURS



FIVE SIZES



TWO FINISHES

Atrium is both simple and strong, with a stormy palette of four colours that deliver room-defining character. With numerous large format sizes available in both a Natural and Grip finish, this range captures the effect of concrete to deliver a modern, industrial look. The Grip finish offers a PTV slip resistance rating of 36+, making Atrium the perfect choice for high-traffic, large open spaces.





COLOURS AND PRODUCT CODES

V3: Moderate to High Shade Variation



CLAY PEI: IV LRV: 40

Product Code: N ATRMIN + G ATRMIG | Mosaic Code: N ATRMIM | Fitting Code: N ATRMIS



PRALINE PEI: IV LRV: 24

Product Code: N ATRM2N + G ATRM2G | Mosaic Code: N ATRM2M | Fitting Code: N ATRM2S

COLOURS AND PRODUCT CODES

V3: Moderate to High Shade Variation



PUMICE PEI: IV LRV: 29

Product Code: N ATRM3N + G ATRM3G | Mosaic Code: N ATRM3M | Fitting Code: N ATRM3S




GRAPHITE PEI: IV LRV: 18

Product Code: N ATRM4N + G ATRM4G | Mosaic Code: N ATRM4M | Fitting Code: N ATRM4S

SIZE FORMATS AND AVAILABILITY

Size Options and Packing Information



#	Size Format	Thickness	Finish	Availability	Class	Pcs / Box	M ² / Box	Kg / Box
01	888x443mm	10mm	Natural	All Colours Shown	Bla	2 Tiles	0.78 m ²	17.72 kg
02	592x592mm	10mm	Natural	All Colours Shown	Bla	3 Tiles	1.05 m ²	23.20 kg
			Grip	All Colours Shown	Bla	3 Tiles	1.05 m ²	23.20 kg
03	592x295mm	8.5mm	Natural	All Colours Shown	Bla	7 Tiles	1.22 m ²	22.60 kg
			Grip	All Colours Shown	Bla	7 Tiles	1.22 m ²	22.60 kg
04	450x450mm	8.5mm	Natural	All Colours Shown	Bla	5 Tiles	1.02 m ²	19.20 kg
05	300x300mm Square Mosaic	8.5mm	Natural	All Colours Shown	Bla	11 Sheets	0.99 m ²	18.40 kg

#	Fittings	Thickness	Finish	Availability	Class	Pcs / Box	Lm / Box	Kg / Box
06	592x80mm R/T Skirting	10mm	Natural	All Colours Shown	Bla	6 Tiles	3.55 lm	6.00 kg
07	450x80mm R/T Skirting	8.5mm	Natural	All Colours Shown	Bla	28 Tiles	12.60 lm	20.00 kg

Note: Glazed Porcelain / Bla tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - www.johnson-tiles.com. (R) Rectified Edge.



Pumice Natural 592x295x8.5mm - ATRM3N

TECHNICAL SUPPORT

Specification, Sustainability and Important Information

Product Specification

Range Name	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	Material / Class
Atrium	Natural	Internal and External	Internal Only	-	Glazed Porcelain / Bla
	Grip	Internal and External	Internal and External	Yes	Glazed Porcelain / Bla

Floor Values

Finish	Colour	PTV (96)	PTV (55)	R Value	Wet Ramp	PEI	Traffic
Natural	All Colours Shown	Wet 25 - 35	-	R9	-	IV	Commercial
Grip	All Colours Shown	Wet 36+	Wet 36+	R11	-	IV	Commercial

Physical Properties - Glazed Porcelain / Bla

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
Length / Width EN ISO 10545-2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	Modulus of Rupture EN ISO 10545-4	Min. 35N / mm ²	Pass
Thickness EN ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	Thermal Shock EN ISO 10545-9	Pass	Pass
Straightness of Side EN ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	Frost Resistance EN ISO 10545-12	Resistant	Resistant
Rectangularity EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Chemical Resistance EN ISO 10545-13	Min. Class B	Pass
Surface Flatness EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Stain Resistance EN ISO 10545-14	Min. Class 3	Pass
Water Absorption EN ISO 10545-3	$\leq 0.5\%$	Pass	Fire Rating		Class A1 FL Non Combustible

Sustainability Credentials

Range Name	Material / Class	EPD	Recycled Content - Tiles	Recycled Content - Packaging
Atrium	Glazed Porcelain / Bla	Yes	Up to 20%	Up to 100% (Boxes Only)

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. Please contact our technical helpline, or visit our website for specification and installation advice. All floor tiles shown in this literature achieve a PTV (96) Dry 36+ test result. PTV (96): Pendulum Test Value - 4S. PTV (55): Pendulum Test Value - TRL. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute. EPD: Environmental Product Declaration. CSV: Colour Shade Variation.

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour and patterning are acceptable.

The tiles shown in this literature are quality products and conform to BS EN 14411 as shown in the physical properties listed above.

For a comprehensive colour, size, finish and availability overview along with full technical and sustainability information for all products shown, please visit our website - www.johnson-tiles.com

- All sizes listed are metric modular.
- For specific suitability details, please contact our technical advice helpline or use the email address provided.
- Johnson Tiles Limited cannot accept responsibility for any tiles that have already been fixed.
- Johnson Tiles Limited reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

All product technical values quoted in this literature are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles Limited are British Standard registered. To find out more, please contact our technical advice helpline on +44 (0)1782 524 111 or email: technical@johnson-tiles.com.

WHERE TO FIND US

Head Office

Harewood Street, Tunstall,
Stoke on Trent, Staffordshire,
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575
Email: info@johnson-tiles.com
www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street,
London, W1W 8BB,
United Kingdom

Tel: +44 (0)20 7436 8629
Email: info@material-lab.co.uk
www.material-lab.co.uk

Factory Outlet

Tel: +44 (0)1782 524 040
Email: foutlet@johnson-tiles.com
www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0)1782 524 000
Email: sales@johnson-tiles.com
8:30am - 4:30pm (Monday - Friday)

Order A Sample

Tel: +44 (0)1782 524 043
Email: samples@johnson-tiles.com

Technical Advice Helpline

Tel: +44 (0)1782 524 111
Email: technical@johnson-tiles.com

Updated: October 2024



© 2024 Johnson Tiles Limited