

DECLARATION OF PERFORMANCE

No. 47-27 / 1-CPR/2021

- Unique identification code of the product type:
MULTI-FLEX ADHESIVE - WHITE (47-27)
- Batch / serial No. identifying the construction product as required under Article 11(4)
NB. Batch number is printed on the side of the bag with date of manufacture.
- Intended use in accordance with the harmonised standard:
Improved deformable fast setting cementitious adhesive with reduced slip and extended open time for internal & external tiling
- Name & contact address of the Manufacturer:
**PALACE CHEMICALS Ltd
Speke Hall Industrial Estate; Speke; Liverpool
L24 1YA**
- Name & contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)
Not applicable
- System of assessment & verification of constancy of performance as set out in Annex V:
System 3
- Harmonised EN Standard:
EN 12004:2007 + A1:2012
The notified body No. NB1289 CERAM (LUCIDEON) performed the test according to EN 12004:2007 + A1:2012 under system 3 and issued the following report:
Test report (104751)-22376.
- Declared Performance:
To harmonised technical specification: EN 12004:2007 + A1:2012

| Essential characteristics | Performance | Harmonised technical specification |
|---|---|------------------------------------|
| Bond strength as: <ul style="list-style-type: none"> Early tensile adhesion strength Initial Tensile adhesion strength | > 0.5 N/mm ² > 1.0 N/mm ² | EN 12004:2007 + A1:2012 |
| Extended open time tensile adhesion strength: <ul style="list-style-type: none"> Tensile strength after 30 minutes open time | > 0.5 N/mm ² | |
| Durability for: <ul style="list-style-type: none"> Tensile adhesion strength after heat ageing Tensile adhesion strength after freeze thaw cycles Tensile adhesion strength after water immersion | > 1.0 N/mm ² > 1.0 N/mm ² > 1.0 N/mm ² | |
| Reaction to Fire Reduced Slip Deformability | Class E < 0.5mm > 2.5mm | |
| Release of dangerous substances | See MSDS | |

- Declaration:
The performance of the above product identified in points 1 & 2 is in conformity with the declared performance as defined under EN 12004:2007 + A1:2012. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for & behalf of
Palace Chemicals Ltd:

Jim Percival - Technical Director – Palace Chemicals Ltd

Date: 21st June 2021